

(43) International Publication Date 11 January 2001 (11.01.2001)

PCT

(10) International Publication Number WO 01/03462 A1

- (51) International Patent Classification7:
- ____

H04Q 7/38

- (21) International Application Number: PCT/EP00/06170
- (22) International Filing Date: 30 June 2000 (30.06.2000)
- (25) Filing Language:

English

(26) Publication Language:

English

- (30) Priority Data: 9915841.2
- 6 July 1999 (06.07.1999) GB
- (71) Applicant (for all designated States except US): NOKIA NETWORKS OY [FI/FI]; Keilalahdemie 4, FIN-02150 Espoo (FI).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): KALLIOJÄRVI, Kari [FI/FI]; Peräläntie 6, FIN-02880 Veikkola (FI).


- (74) Agents: RUUSKANEN, Juha-Pekka et al.: Page White & Farrer, 54 Doughty Street, London WC1N 2LS (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI. GB, GD, GE, GH, GM, HR, HU, ID, IL, IN. IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

With international search report.

[Continued on next page]

(54) Title: LOCATION OF A MOBILE STATION IN A TELECOMMUNICATION SYSTEM



(57) Abstract: Means and a method for determination of a distance between a transmitting station and a receiving station is disclosed. In the method a characteristic parameter is determined for the radio propagation environment of the receiving station. At least one feature of a signal that has been received at the receiving station is measured, said feature being such that it can be used for the determination of the distance between the stations. The distance is then computed based on said measured signal feature and the characteristic parameter.

HOULDON MUZDLONE

O 01/03462 A